



DS 300

Track asset access with ease.

ORBCOMM's wireless door sensor delivers enhanced visibility of trailer and container operations and improved cargo security. It detects when doors open or close, enabling fleet operators to know if the cargo area is being accessed as scheduled and react quickly to unexpected openings.

Hassle-free installation and maintenance

No wires means it's easy to install, maintain and repair, making it the ideal fit for large deployments. Get up and running faster with our intuitive Field Support Tool mobile app for device configuration and support.

Ruggedised

Built IP67-rated to withstand harsh operating environments with dust, humidity, water, shock and vibration for reliable reporting virtually anywhere.

Around-the-clock monitoring

Receive alerts when unexpected door events occur, openings take place outside geofence locations or when a sensor is damaged.

Long service life

Up to five years of reporting without having to change batteries for minimal upkeep.

Enhanced cargo security

Durable

Part of a comprehensive solution

Quick and wireless installation

Long battery life

Mobile app support for simple configuration

Specifications

Compatibility

- CT 1000
- ST 9100
- GT 1100
- GT 1200
- AG 400

Environmental conditions

- Operating Temperature: -40 °C to +85 °C
- Dust and water ingress: IP67
- Vibration: SAE J1455 (Sec 4.10.4.2 figures 6-8)
- Shock: MIL-STD-810G (Sec 516.6 procedure I, Section 2.3.2c)

Communications

- Bluetooth Low Energy (BLE) version 4.0
- Low power, short range protocol using 2.4GHz band

Mechanical

- Dimensions: 102 mm x 64 mm x 15 mm
- Weight: 97g

Power

- Lithium battery with 1000 mAh capacity
- Up to 5 years of operation

Ordering details

- ST100687-001 – Door sensor with mounting bracket required for rolled doors
- ST100547-001 – Door sensor

Certification and compliance

- CE Mark:
 - ▶ EN 301 489-17
 - ▶ EN 301 489-1 (EMC)
 - ▶ IEC 62368
- FCC regulation: 47 CFR 15
- Industry Canada
 - ▶ ICES-003
- RoHS
- GAMP 5¹

1 – When used in combination with the MX2



A sample DS 300 deployment

Although we strive to ensure accuracy in all of our published specifications, actual field performance can vary depending on a variety of environmental, installation and usage factors, as well as third-party factors such as cellular providers. The specifications listed are approximations, and do not constitute binding statements or modify the terms and conditions of purchase or lease including, but not limited to, product operational limitations and warranties. All specifications are subject to change without notice. Please check www.orbcomm.com to ensure you have the latest version of these specifications.

Email: sales@ORBCOMM.com | Call: 1-800-ORBCOMM

Visit our website www.ORBCOMM.com

ORBCOMM is a pioneer in IoT technology, empowering customers with insight to make data-driven decisions that help them optimize their operations, maximize profitability and build a more sustainable future. With 30 years of experience and the most comprehensive solution portfolio in the industry, ORBCOMM enables the management of over a million assets worldwide for a diverse customer base spanning transportation, supply chain, heavy equipment, maritime, natural resources and government. For more information about how ORBCOMM is driving the evolution of industry through the power of data, visit www.orbcomm.com.